

# Fork clamp

constant sideshift +/- 100 mm, bolt-on forks

type	lift truck capacity tons	ISO	capacity on forks kg/mm LC	capacity as clamp kg/mm LC	A III mm	B mm	forks b x h x l mm	sideshift mm	V LLC mm	ESP COG mm	weight kg
PGK 15-S	1,0-1,5	II	1400/500	1200/500	360-1510 360-1580	980 1050	100x40x1200	+/- 100	143	210 202	355 365
PGK 25-S	2,0-2,5	II	2400/500	1900/500	310-1460 310-1530 310-1630 70-1150 310-1680 310-1880	980 1050 1150 1150 1200 1400	125x45x1200	+/- 100	143	222 218 215 212 217 205	425 435 450 445 455 485
PGK 30-S	3,0	III	2900/500	2400/500	310-1460 310-1530 310-1630 210-1430 310-1680 310-1780 310-1830 310-1930	980 1050 1150 1150 1200 1300 1350 1450	125x50x1200	+/- 100	143	220 215 210 210 212 210 205 205 200	445 455 470 465 480 490 500 515
PGK 35-S	3,5	III	3600/500	2700/500	260-1580 260-1680 260-1780	1150 1250 1350	150x50x1200	+/- 100	153	240 237 235	530 550 570
PGK 40-S	4,0	III	4100/500	2900/500	250-1660 250-1760 250-1860	1250 1350 1450	150x50x1200	+/- 100	155	215 210 202	680 700 720
PGK 45-S	4,5-5,0/500	III	4500/600	3500/500	250-1660 250-1760 250-1860	1250 1350 1450	150x60x1200	+/- 100	165	210 205 204	720 740 760
PGK 48-S	5,0/600	III	4800/600	3500/600	250-1700 250-1800 250-1900	1350 1450 1550	150x70x1200	+/- 100	175	230 225 220	830 850 860

- features bolt-on forks as standard
- includes hoses and couplings
- 2 hydraulic functions required
- toe-in on forks as standard
- sideshift with bottom rollers as standard
- cylinder protection upon request
- includes protection strip

class IV see next page