



Fork positioner for reach truck, no sideshift



The fork positioner range **RZV/RZV G** features bar guides and can be used also with long forks. The well balanced frame design offers durability and excellent visibility. This model range features a small frame that supports the configuration of reach trucks. Clamping of goods is not allowed.



Important note: The reach truck must be equipped with a collision prevention that prevents collision of fork positioner parts with the wheel legs or parts of the reach truck. This means usually that fork positioning and sideshift must be shut off with the attachment between the wheel legs. The reach truck carriage design must accommodate the mounting of an attachment. A spacer kit is available from Durwen, see bottom, that allows the extension of the attachment mounting up to 50mm to allow for carriage parts or reach truck parts that may protrude into the attachment mounting or operation space.

fork positioner for reach truck, no sideshift, fork adaptors, small frame

type	lift truck capacity tons	capacity kg/mm LC	ISO	B mm	A mm	b x h x l mm	V LLC mm	ESP COG mm	weight kg
RZV 25	1,5-2,5	2500/500	II	750	490-750	120	126	42	100
				800	490-800				110
				850	490-850				120
				880	490-880				125
RZV 28	2,5/600	2500/600	II	750	490-750	120	126	39	110
				800	490-800				115
				850	490-850				125
				880	490-880				130



Important note: The reach truck must be equipped with a collision prevention that prevents collision of fork positioner parts with the wheel legs or parts of the reach truck. This means usually that fork positioning and sideshift must be shut off with the attachment between the wheel legs. The reach truck carriage design must accommodate the mounting of an attachment. A spacer kit is available from Durwen, see bottom, that allows the extension of the attachment mounting up to 50mm to allow for carriage parts or reach truck parts that may protrude into the attachment mounting or operation space.

fork positioner for reach truck, no sideshift, bolt-on forks, small frame

type	lift truck capacity tons	capacity kg/mm LC	ISO	B mm	A mm	b x h x l mm	V LLC mm	ESP COG mm	weight kg
RZV 16 G	1,6	1600/500	II	750	470-730	100x40x1200	126	285	198
				800	470-780				208
				850	470-830				218
				880	470-860				223
RZV 20 G	2,0	2000/500	II	750	470-730	100x45x1200	126	299	210
				800	470-780				220
				850	470-830				230
				880	470-860				235
RZV 25 G	2,5	2500/500	II	750	490-750	120x40x1200	126	307	218
				800	490-800				228
				850	490-850				238
				880	490-880				243
RZV 28 G	2,5/600	2500/600	II	750	495-755	125x45x1200	126	326	238
				800	495-805				248
				850	495-855				258
				880	495-885				263

- Includes connection hoses and couplings
- 1 hydraulic function required
- Backrest see accessories
- Sideshift upon request
- LLC spacer kit (can increase LLC in steps up to 50 mm) upon request
- Different frame widths upon request